

# SSV KS: 性能表

幫浦型號：40SSV26.75 — 馬力：KW

口徑  
幫浦型式  
頻率：6-60 HZ  
5-50 HZ  
極數：2-2 pole  
4-4 pole

## 2P(2極)三相性能表 60HZ 3450RPM

揚總程(公尺M)，不計入口真空壓力，出水量(公升/分LPM)，馬力(HP)

編號	型號	馬力	口徑	10M	15M	20M	25M	30M	35M	40M	45M	50M	55M	60M	65M	70M	75M	80M
1	25SSV26.37	1/2	1"	110	40													
2	25SSV26.75	1	1"	150	110	70												
3	40SSV26.75	1	1.5"	192	160													
4	40SSV26.75H	1	1.5"	180	150	140												
5	40SSV26.75Q	1	1.5"	280	150													
6	40SSV261.5	2	1.5"	316	289	210												
7	40SSV262.2	3	1.5"	325	312	300	275	194										
8	40SSV263.7	5	1.5"	338	323	309	295	255	216	157								
9	50SSV261.5	2	2"	316	289	210												
10	50SSV262.2	3	2"	382	367	350	323	229										
11	50SSV262.2Q	3	2"	483	454	402	320	239										
12	65SSV262.2	3	2.5"	580	450	300												
13	50SSV263.7	5	2"	395	380	369	356	341	312	279								
14	65SSV263.7	5	2.5"	623	570	496	360											
15	80SSV263.7	5	3"	623	570	496	360											
16	80SSV263.7H	5	3"	804	780	703	617	414										
17	50SSV265.5	7.5	2"	417	410	402	389	378	362	347	326	296	260	207				
18	80SSV265.5	7.5	3"	895	875	820	750	620	450									
19	100SSV265.5	7.5	4"	1469	1100	900												
20	50SSV267.5	10	2"	480	470	460	439	450	440	430	419	410	390	380	350	320	207	
21	80SSV267.5	10	3"	975	910	850	780	740	670	580	420							
22	100SSV267.5	10	4"	1650	1315	1100												
23	125SSV267.5	10	5"	1640	1340													
24	50SSV2611	15	2"							564	523	550	544	496	470	450	357	226
25	80SSV2611	15	3"	1160	1150	1070	1030	990	920	850	750	670	560	330				
26	100SSV2611	15	4"	1665	1615	1475	1250	995										
27	125SSV2611	15	5"	2065	1860	1595												
28	80SSV2615	20	3"	1160	1150	1070	1030	995	940	890	820	760	670	580	350			
29	100SSV2615	20	4"	1810	1790	1760	1690	1550	1315	955								
30	125SSV2615	20	5"	2200	2170	2120	1935	1690										
31	100SSV2618.5	25	4"	1710	1642	1582	1534	1452	1356	1172	965	767	664	443				
32	125SSV2618.5	25	5"	3200	2600	2100	1350	850										
33	150SSV2618.5	25	6"	4015	3580	3050	2320											
34	100SSV2622	30	4"			1672	1657	1600	1512	1534	1435	1253	1107	1107	990	793		
35	125SSV2622	30	5"	3560	3000	2400	1550	1130	800									
36	150SSV2622	30	6"	4560	4010	3600	3075	2330										
37	100SSV2630	40	4"	1965	1930	1910	1885	1860	1850	1835	1810	1760	1740	1710	1610	1400	1165	
38	100SSV2637	50	4"		1965	1930	1910	1885	1860	1850	1835	1810	1760	1740	1710	1610	1400	1165
39	125SSV2630	40	5"	3950	3450	2675	1850	1250	900									
40	150SSV2630	40	6"	4950	4910	4840	4630	3695	3165	2440								

SHIN KANG PUMP